



EST. 1798

J. Gibson McIlvain Co.

FINE IMPORTED & DOMESTIC WOOD PRODUCTS



ALPHA

BY J. GIBSON McILVAIN CO.

The A-List Finished Wood Products

ANDAMAN

TEAK TRADEWINDS COLLECTION

Manufactured from smooth Plantation Teak, Andaman has high variability in appearance. The material is sourced with sustainable methods from across Asia and boasts a higher grade than what the market has come to expect from plantation offerings. This product is utilized in exterior applications for cladding, soffits, ceilings, and decking. FSC Material is available upon request for this look.

TECH SPECS

Janka Hardness: 1000 lbs

Fire Rating: Class B

Durability: Class 1

Movement:

Radial Shrinkage: 3%

Tangential Shrinkage: 6%

Grade: FAS

Finish:

Oil-Based Wood Stabilizer

- Finished on 1 show face and sealed on back and sides unless otherwise noted

VOC Range: 215 g/L

Width: up to 6"

Thickness: 5/8 - 1"

Length: up to 9'

Variability Score: 5

For use in **exterior** applications

INSTALLATION

Alpha Cladding is compatible with the following installation methods:

- Clip Systems
- Hidden Fasteners
- Visible Fasteners

A proper acclimation period is required once material is received to ensure best results.

Rear ventilation is required to minimize movement. Utilize furring strips to create a minimum 3/8" gap.

CARE & MAINTENANCE

Plan to inspect cladding annually to determine if reapplication is needed. In shaded areas or ceiling/soffit applications, reapplication may not be as frequent. Please refer to our full care & maintenance instructions for more information.

CERTIFICATIONS &

LEED ELIGIBILITY

- **FSC** material* available upon request
 - **LEED Eligibility:**
 - o 2 Points: MR7 Materials & Resources | Sourcing of Raw Materials
 - Other points available for site-specific attributes
- *specifying FSC material may increase lead times and cost

Profiles:

- T&G (V-Groove, Square Edge, Nickel Gap w/ crush bead)
- Shiplap
- Rainscreen
- S4S
- Custom Profiles available upon request

