



EST. 1798

J. Gibson McIlvain Co.

FINE IMPORTED & DOMESTIC WOOD PRODUCTS



ALPHA

BY J. GIBSON McILVAIN CO.

The A-List Finished Wood Products

MYAKKA

TEAK TRADEWINDS COLLECTION

Manufactured from smooth Afrormosia, Myakka has low variability in appearance. The material is sourced with sustainable methods from West Africa and is a widely accepted Teak alternative. This product is utilized in exterior applications for cladding, soffits, ceilings, and decking. FSC Material is available upon request for this look.

TECH SPECS

Janka Hardness: 1570 lbs

Fire Rating: Class B

Durability: Class 1

Movement:

Radial Shrinkage: 3.2%

Tangential Shrinkage: 6.2%

Grade: FAS

Finish:

Oil-Based Wood Stabilizer

- Finished on 1 show face and sealed on back and sides unless otherwise noted

VOC Range: 215 g/L

Width: up to 10"

Thickness: 5/8 - 1"

Length: up to 20'

Variability Score: 2

For use in **exterior** applications

INSTALLATION

Alpha Cladding is compatible with the following installation methods:

- Clip Systems
- Hidden Fasteners
- Visible Fasteners

A proper acclimation period is required once material is received to ensure best results.

Rear ventilation is required to minimize movement. Utilize furring strips to create a minimum 3/8" gap.

CARE & MAINTENANCE

Plan to inspect cladding annually to determine if reapplication is needed. In shaded areas or ceiling/soffit applications, reapplication may not be as frequent. Please refer to our full care & maintenance instructions for more information.

CERTIFICATIONS &

LEED ELIGIBILITY

- **FSC** material* available upon request
 - **LEED Eligibility:**
 - o 2 Points: MR7 Materials & Resources | Sourcing of Raw Materials
 - Other points available for site-specific attributes
- *specifying FSC material may increase lead times and cost

Profiles:

- T&G (V-Groove, Square Edge, Nickel Gap w/ crush bead)
- Shiplap
- Rainscreen
- S4S
- Custom Profiles available upon request

