



EST. 1798

**J. Gibson McIlvain Co.**

FINE IMPORTED & DOMESTIC WOOD PRODUCTS



**ALPHA**

BY J. GIBSON McILVAIN CO.

The A-List Finished Wood Products

**PASADENA**

**PACIFIC COLLECTION**

Manufactured from smooth Mixed Grain Jatoba, Pasadena has a medium variability in appearance. The material is sourced with sustainable methods from Brazil and is a widely known in America as "Brazilian Cherry". This product is utilized in exterior applications for cladding, soffits, ceilings, and decking. FSC Material is available upon request for this look.

## TECH SPECS

**Janka Hardness:** 2690 lbs

**Fire Rating:** Class A

**Durability:** Class 1

**Movement:**

Radial Shrinkage: 3.8%

Tangential Shrinkage: 7.1%

**Grade:** FAS

**Finish:**

Oil-Based Wood Stabilizer

- Finished on 1 show face and sealed on back and sides unless otherwise noted

**VOC Range:** 215 g/L

**Width:** up to 6"

**Thickness:** 5/8 - 1"

**Length:** up to 22'

**Variability Score:** 3

For use in **exterior** applications

## INSTALLATION

Alpha Cladding is compatible with the following installation methods:

- Clip Systems
- Hidden Fasteners
- Visible Fasteners

A proper acclimation period is required once material is received to ensure best results.

**Rear ventilation is required** to minimize movement. Utilize furring strips to create a minimum 3/8" gap.

## CARE & MAINTENANCE

Plan to inspect cladding annually to determine if reapplication is needed. In shaded areas or ceiling/soffit applications, reapplication may not be as frequent. Please refer to our full [care & maintenance](#) instructions for more information.

## CERTIFICATIONS &

### LEED ELIGIBILITY

- **FSC** material\* available upon request
  - **LEED Eligibility:**
    - o 2 Points: MR7 Materials & Resources | Sourcing of Raw Materials
  - Other points available for site-specific attributes
- \*specifying FSC material may increase lead times and cost

## Profiles:

- T&G (V-Groove, Square Edge, Nickel Gap w/ crush bead)
- Shiplap
- Rainscreen
- S4S
- Custom Profiles available upon request

