



Manufactured from smooth Iroko, San Gabriel has low variability in appearance. The material is sourced with sustainable methods from West Africa and has been appropriately nicknamed "African Teak" due to its similarities to Teak in appearance and performance. This product is utilized in exterior applications for cladding, soffits, ceilings, and decking. FSC Material is available upon request for this look.

# **TECH SPECS**

#### Janka Hardness: 1260 lbs Fire Rating: Class B **Durabilty:** Class 1 **Movement:** Radial Shrinkage: 2.8% Tangential Shrinkage: 3.8%

Grade: FAS

#### Finish:

**Oil-Based Wood Stabilizer** 

- Finished on 1 show face and sealed on back and sides unless otherwise noted

VOC Range: 215 g/L

Width: up to 10" Thickness: 5/8 - 1" Length: up to 20' Variability Score: 2

For use in **exterior** applications

# INSTALLATION

Alpha Cladding is compatible with the following installation methods:

- Clip Systems
- Hidden Fasteners
- Visible Fasteners

A proper acclimation period is required once material is received to ensure best results.

Rear ventilation is required to minimize movement. Utilize furring strips to create a minimum 3/8" gap.

### **CARE & MAINTENANCE**

Plan to inspect cladding annually to determine if reapplication is needed. In shaded areas or ceiling/soffit applications, reapplication may not be as frequent. Please refer to our full care & maintenance instructions for more information.

### **CERTIFICATIONS &** LEED ELIGIBILITY

- FSC material\* available upon request
- LEED Eligibility:
  - 2 Points: MR7 Materials & Resources | Sourcing of Raw Materials
- Other points available for site-specific attributes

\*specifying FSC material may increase lead times and cost

ge, Nickel	.6875 in	Crush E	Bead	.7 iı	
upon	.7 in			.7 in	

#### **Profiles:**

- T&G (V-Groove, Square Edg Gap w/ crush bead
- Shiplap
- Rainscreen

-	S49	5
	-	

- Custom Profiles available u request

www.mcilvain.com | (410) 335-9600