



Manufactured from lightly textured CVG Western Red Cedar, Southampton has high variability in appearance. The material is sourced with sustainable methods from the US and Canada and is a proven exterior cladding species. This product is utilized in exterior and interior applications for cladding, soffits, ceilings, and wall panels. FSC Material is available upon request for this look.

TECH SPECS

Janka Hardness: 350 lbs

Fire Rating: Class B **Durabilty: Class 2**

Movement:

Radial Shrinkage: 2% Tangential Shrinkage: 5%

Grade: FAS

Finish:

Semi-Solid Water-Based

- Finished on 1 show face and sealed on back and sides unless otherwise noted

VOC Range: < 100 g/L

Width: up to 6" Thickness: 5/8 - 1" Length: up to 12' **Variability Score:** 5

For use in **exterior and interior**

applications

INSTALLATION

Alpha Cladding is compatible with the following installation methods:

- Clip Systems
- Hidden Fasteners
- Visible Fasteners

A proper acclimation period is required once material is received to ensure best results.

Rear ventilation is required to minimize movement. Utilize furring strips to create a minimum 3/8" gap.

CARE & MAINTENANCE

Plan to inspect cladding annually to determine if reapplication is needed. In shaded areas or ceiling/soffit applications, reapplication may not be as frequent. Please refer to our full care & maintenance instructions for more information.

www.mcilvain.com | (410) 335-9600

CERTIFICATIONS & LEED ELIGIBILITY

- FSC material* available upon request
- LEED Eligibility:

lead times and cost

- 2 Points: MR7 Materials & Resources | Sourcing of Raw Materials
- Other points available for site-specific attributes *specifying FSC material may increase

- T&G (V-Groove, Square Edge, Nickel Gap w/ crush bead
- Shiplap
- Rainscreen
- Custom Profiles available upon request

